

SECTION 01070

CUTTING AND PATCHING

3. Necessity for cutting or alteration.
4. Description of proposed work, and products to be used.
5. Alternatives to cutting and patching.
6. Effect of work on Owner or separate contractor.
7. Written permission of affected separate contractor.
8. Date and time work will be executed.

PART 2 PRODUCTS

2.01 MATERIALS

- A. Primary Products: Those required for original installation.
 1. When cutting and patching into existing exposed masonry walls, utilize salvaged materials to provide seamless match to existing conditions.
- B. Product Substitution: For any proposed change in materials, submit request for substitution under provisions of Section 01000 General Requirements.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Inspect existing conditions prior to commencing work, including elements subject to damage or movement during cutting and patching.
- B. After uncovering existing work, inspect conditions affecting performance of work.
- C. Beginning of cutting or patching means acceptance of existing conditions.

3.02 PREPARATION

SECTION 01070

CUTTING AND PATCHING

- G. Refinish surfaces to match adjacent finish. for continuous surfaces, refinish to nearest intersection or natural break. For an assembly, refinish entire unit.
- H. Where existing products of other Sections are removed, i.e. electrical switches, the General Contractor shall patch masonry and finish to match the existing.
- I. Where new masonry walls are created the General Contractor shall provide vinyl base to match existing.

END OF SECTION